



SHIMMER

A room with a view

Looking for a compact but spacious tent, with just that little bit of extra comfort? Look no further! Our Shimmer glamping tent is ideal for people who do not normally 'do' camping – and for those that do.

The Shimmer has two floors, which means you can provide your guests with a spacious living area. There is a kitchen with a dining table on the ground floor, or the design can be configured as a compact kitchen or a bathroom. On the first floor, you will find a separate bedroom with a spacious veranda, where your guests can relax and simply enjoy the view.

It is perfect for couples looking for a romantic break and wanting to get close to nature, but it is also an excellent choice for walkers and cyclists who need a practical, yet comfortable base.

- ✔ The Shimmer offers a lot of space on a small footprint due to the extra floor
- ✔ Various efficient layouts are possible
- ✔ Spacious, yet compact – ideal for sites with smaller spaces
- ✔ Guests can make the most of your fantastic views from the upper floor

FLOORPLAN SHIMMER

Dimensions

Inner tent ground floor	7,5 m ²	2.5 x 3 m
Veranda ground floor	22,5 m ²	7.5 x 3 m
Inner tent first floor	7.5 m ²	2.5 x 3 m
Veranda first floor	6,5 m ²	1,5 x 5 m
Total surface	30 m ²	5 x 6 m
Footprint	36 m ²	5 x 7.2 m

Features

# Guests	2
# Bedrooms	1
Bathroom	Optional
Kitchen	Yes

Floorplan 3D



Floorplan 2D



PHOTOS SHIMMER



SPECIFICATIONS SHIMMER

Elements	Colour	Specifications	Technical standards
PVC Roof	Beige Brown Green	UV and flame retardant PVC 650gr/m ² . The PVC is easy to clean and meets the stringent European, British and American fire regulations (M2, B1 and DIN 4102 standard).	BS 7837 DIN 4102 – Class B1 M2 Classification NFP 92-503 EN 13501-1 B-s3, d0 Total weight DIN and ISO 2286-2 – 650 gr/m ²
Flame retardant Polyester (FPTC420)	Khaki	Flame retardant 420 gr/m ² . The fibers in this fabric provide extra security and protection. It is scorch, glow and spark resistant. Textile material that is flame retardant has an inhibiting effect on the occurrence of fire and slow fire spreading.	Weight 420gr/m ² + 5% Standarder width: 150 cm Tearing strenght: ±10% - Warp: 79N - Weft: 53N Tensile strength: ± 10% - Warp: 2800N/5 cm - Weft: 2232N/5 cm Watercolumn: ≥ 400mm Color fading level: GR6 ISO105B04-1994 Mildewtreated: Level 0 AATCC30-2017 Fireproof level: M2 BS7837-1996
KA-46	Khaki	TenCate PolyCotton consists of a perfect blend of 50/50 cotton and polyester. The fibre mixed in the yarn provides a very even performance. The breathable and moisture regulation properties of cotton are complemented by the extra strength and durability of polyester for intensive use, without sacrificing a natural feel.	50% Polyester, 50% cotton Water- and dirtrepellent Width: 205 cm Weight 420 gr/m ² (+/- 5%) Tensile strength Warp (5 cm) 160 daN Weft (5 cm) 120 daN Tearing strength Warp (4,3 cm) 6,0 daN Weft (4,3 cm) 3,5 daN Watercolumn ≥45 cm Colour-weather fastness ≥4
Fixing		The inner tent hanging system is a unique system. It has no point loading, so the weight is equally distributed across the surface of the structure.	
Construction		The connectors of the construction are made from 2.9mm hot dipped galvanized steel. The poles have a dia of 80 or 100mm.	

Why choose us?

It's all in the detail. Our beautiful, sustainable glamping tents are not mass produced, but are created by a team of specialists with a passion for outdoor living. We personally manage every aspect, from the initial concept and product design, to the sourcing of eco-friendly materials and construction, to quality control. And it doesn't stop there, we provide ongoing service and support, long after you bought your tent or lodge.

Interested?

Get in touch to find out more about our tents, or come and see them for yourself. Email us on sales@yalacanvaslodges.com and we'll get right back to you or call us on +31 (0) 527 620 325.

More info about the materials

[Video about Polycotton Ka46](#)

